



19"-Rack Cabinet 37RU 600x800 mm

The 37RU rack Cabinet is used for the housing of active or passive equipment, visible from the outside and protected by a safe steel lockable structure. Compatible with optical fiber, data cables or coaxial cable installations, it allows the grouping of different technologies in a single cabinet. It is suitable for GPON headends installation, where the infrastructure requires greater depth (up to 800mm depth). The rack is equipped with depth-adjustable side profiles, which allow the installation of different types of panels or equipment. It has a front and rear door, reversible and removable with flexible adjustment, which facilitates working in the rack. The tempered glass front door allows viewing the status of the devices without opening the rack. It also has push-button removable side doors for access to the rack interior through the sides, an advantage when configuring rear connections.

Designed for floor installation. It includes 4 screw-on legs, they allow height regulation, from 45 to 80mm, simplifying the adjustment on inclined or uneven surfaces

Ref.	533138
Logical ref.	MSR1937-68B
EAN13	8424450237342

Other features

Supply method	Disassembled
Rack depth	800mm
Height (RU)	37RU
Perforated doors	

Packaging info

Box	1 pcs.
------------	--------

Physical data

Net weight	86,000.00 g
Gross volume	586.00 dm³
Gross weight	92,000.00 g
Width	600.00 mm
Height	1,790.00 mm
Depth	800.00 mm
Main product weight	86,000.00 g

Highlights

- High strength and durability: made of steel, with a coating based on polyester resins and lead-free pigments
- Safety: Tempered glass, lockable hinged front door
- Laser marking: numerical identification of each "RU"
- Horizontal cable guides: 1U cable panels located at the top and bottom of the cabinet to lead cabling from one side to the other and facilitate connections
- Electrical safety: Each door and removable panel includes a grounding screw (terminal) to ensure proper grounding connection
- A 120x120mm ventilation kit can be incorporated for the installation of active equipment, such as headends
- High load capacity: supports up to 1000 kg when installed on the floor
- Black colour (RAL 9004)

Discover

REF.	DIMENSIONS (mm)	RACK UNITS (RU)	INSTALLATION	COMPATIBLE WITH			
Compatibility of our racks with fans, wheels, plinths and cable management				FAN	WHEELS	PLINTH	CABLE MANAGEMENT

533105/06	600x450	6+2	The correct selection of accessories in a rack is key to ensuring the performance, accessibility and organisation of the entire infrastructure. Elements such as fans, wheels, plinths and cable management panels help optimise cooling, mobility and cable routing.	Wall / Floor	533174	Not applicable	Not applicable
533107/08	600x450	8+2					
533112/13	600x450	13+2					
533114/15	600x450	15+2					
533111/16	600x600	15+2	Our racks are equipped with natural ventilation, but for applications requiring greater thermal control, it is possible to incorporate active ventilation systems with fans, significantly improving thermal management.				533158 533159 533160
533119/18	600x600	18					
533121/22	600x600	22					
533126/27	600x600	27					
533131/32	600x800	32	For standard racks include feet, but it is also possible to add wheels. In this way, a rack can be installed either on feet only, on wheels, or with a combination of both. This configuration provides great flexibility, allowing the rack to be moved easily during installation or maintenance, to correct floor unevenness and to distribute the load across more support points.	Floor	533175		
533136/37	600x600	37					
533138/39	600x800	37					
533141/42	600x800	42					
533128	800x800	27	Another option available for certain racks is installation on plinths. Plinths elevate the cabinet from the floor, making maintenance easier and improving the stability of the assembly. Additional space also allows cable routing and concealment at the bottom section, guiding it neatly towards the rear, contributing to a cleaner and more organised installation.		533176	533401	533158 533159 533160 533166
533143/44	800x800	42					
533149/45	800x800	42					
533148/46	800x1000	42					
533149/47	800x1000	42	Another option for cable management is the use of cable management panels. These enable efficient cable routing inside the rack, facilitating both installation and maintenance operations. Their use improves equipment accessibility and contributes to a more orderly and professional setup. They are available in horizontal and vertical configurations, adapting to the needs of each installation.			533402	Vertical 533167

Below is a compatibility table for our racks with all these accessories:

Technical specifications : Ref. 533138

Modular spacing (standard)	in	19
Height	in	70.472
Width	in	23.622
Depth	in	31.496
Number of rack units (RU)		37
Material		Steel
Rack rail thickness	in	0.079
Color		Black
Surface finishing		Electrostatic powder
Number of doors		2
Front door material		Tempered glass
Rear door		Yes
Rear door material		Steel
Max. load capacity	kg	1000
Max. load capacity (with wheels)	kg	960
Max. load capacity (with legs)	kg	600
Removable sides		Yes
Installation type		Ground
Type of profile rail		L-shaped
Grounding		Yes
Protection index (IP)		20
Protection index (IK)		07