



Splitting Terminal Enclosure Up to 16, fibers

Designed to work as a pass-through and diverting element for optical fiber cables. Commonly used in FTTH projects, inside the buildings (usually in the secondary enclosure).

It can house a total of 16 fibres in its interior, by means of 8 tubes of 2 fibres each. It allows the connectorisation of up to 8 fibres with SC connectors or 16 fibres with LC connectors. Additionally, it has the capacity to house 20 fusions thanks to its two trays of 12 and 8 fusions each.

Ref.	231306
Logical ref.	OVB16
EAN13	8424450321317

Packaging info

Box	1 pcs.
------------	--------

Physical data

Net weight	435.00 g
Gross volume	1.90 dm ³
Gross weight	492.00 g
Width	125.00 mm
Height	235.00 mm
Depth	50.00 mm
Main product weight	435.00 g

Highlights

- Robust material due to ABS plastic construction
- Multi-fiber cable input/output from the main wiring through the side holes
- Easy installation and protection of splices thanks to its 2 independent and folded trays covered by a lid
- Incorporates 8 holders for adapters
- External manipulations are made difficult thanks to the screw lock included on the door
- Protected against dust particles and sprayed rain thanks to its IP53 tightness rating
- Adequate protection for installations with exposure to shocks thanks to its IK08 impact resistance grade
- Includes screws for wall mounting and 8 Heat-shrink fusion protectors for fiber optic splices
- Dimensions (W x H x D): 235mm x 125mm x 50mm
- White colour

Technical specifications : Ref. 231306

Number of fibers			16
Pre-cut openings			No
Independent compartments			No
Closure type			Cover
Front door locking system			Screw
Type of connections			Fusion splice
Installation type			Ceiling
Protection index (IP)			53
Protection index (IK)			08
Grounding			No
Material			ABS Plastic
Color			White
Height		in	9.252
Width		in	4.921
Depth		in	1.969