



Splice Box for 19" Rack 1RU Preassembled with SC Adapters, Singlemode (SM)

Splice Box preassembled with SC Adapters, designed as a distribution and junction point for optical fibers (FO patch panel). It includes an internal tray with capacity to house and organize the splices. Its wide design facilitates easy assembly and maintenance of the splices it houses. Its typical application is to serve as a link between a fixed backbone network and the different elements to which distribution is required. As it is supplied preassembled with adapters and pigtails, installation is simplified and installation time is reduced, since only the corresponding splices are required to interconnect both networks. The position of the tray can be set back with respect to the rack profile, in order to protect the connectors from knocks or chafing and to avoid interfering with the door closure. Available with different adapters.

Ref.	533260
Logical ref.	UFB12SCAPCD-VS
EAN13	8424450333129

Other features

Number of 12 SC/APC Duplex adapters

Physical data

Net weight 1,650.00 g

connectors

Gross volume 7.57 dm³

Gross weight 1,950.00 g

Width 438.00 mm

Height 43.00 mm

Depth 225.00 mm

Main product weight 1,600.00 g

Packaging info

Box 1 pcs.

Carton 5 pcs.

Highlights

- Time saving and easy connection thanks to its preassembled delivery
- Resistant material due to steel construction of frame and rails, with lightweight aluminium base
- Each connector is identified with a laser-marked number
- SC adapters with external self-locking cap and automatic closure, preventing light emission when the adapter is not connected
- Empty spaces in the trays are protected with removable rubber plugs
- Equipped with a FO tray and cover to house the different fiber splices
- Includes clamps and flanges for fixing and guiding the different fibers
- Includes 4 screws and 4 nuts for installation in a 19" rack
- Designed to occupy 1RU
- Black colour (RAL 9005)

Technical specifications : Ref. 533260

Modular spacing (standard)	in	19
Number of rack units (RU)		1
Fiber type		Single-Mode (SM)
Number of connectors		12
Optical connector type		SC Duplex
Max. capacity of connectors		24
Operating temperature	°F	-4 ... 158
Depth	in	8.898
Depth adjustment	in	2.165
Color		Black