



## Replacement for 42RU Rack Double Perforated Steel Door

Perforated double door with honeycomb structure designed for 42RU high 19" racks.

Its construction allows air to circulate freely, helping to keep equipment in optimal temperature conditions. In addition, the perforated design reduces the weight of the door, making it easier to handle, transport and install.

The steel structure provides great strength and durability, guaranteeing the protection of the installed equipment. The door is reversible and removable by means of a flexible snap-fit, allowing it to be adapted to different configurations and easily removed when full access to the inside of the rack is required.

It includes a professional key lock for additional security.

Its design is particularly suitable for installations with limited opening space, providing convenient and secure access even in compact environments.

|              |               |
|--------------|---------------|
| <b>Ref.</b>  | 995301        |
| <b>EAN13</b> | 8424450333013 |

### Packaging info

|            |        |
|------------|--------|
| <b>Box</b> | 1 pcs. |
|------------|--------|

### Physical data

|                     |                       |
|---------------------|-----------------------|
| <b>Net weight</b>   | 13,000.00 g           |
| <b>Gross volume</b> | 75.00 dm <sup>3</sup> |

|                            |             |
|----------------------------|-------------|
| <b>Gross weight</b>        | 14,000.00 g |
| <b>Width</b>               | 805.00 mm   |
| <b>Height</b>              | 1,885.00 mm |
| <b>Depth</b>               | 20.00 mm    |
| <b>Main product weight</b> | 13,000.00 g |

## Highlights

---

- High strength and durability: made of steel and coated with polyester resins and lead-free pigments.
- Convenience: double design reduces opening space requirements
- High ventilation: perforated construction with honeycomb structure keeps equipment at optimum temperature
- Lightweight: optimised design for easy handling, transport and installation
- Reversible and removable: can be adapted to different configurations and removed easily

## Technical specifications : Ref. 995301

|                            |    |                      |
|----------------------------|----|----------------------|
| Modular spacing (standard) | in | 19                   |
| Height                     | in | 74.213               |
| Width                      | in | 31.693               |
| Depth                      | in | 0.787                |
| Number of rack units (RU)  |    | 42                   |
| Material                   |    | Steel                |
| Color                      |    | Black                |
| Surface finishing          |    | Electrostatic powder |
| Number of doors            |    | 2                    |
| Grounding                  |    | Yes                  |
| Protection index (IP)      |    | 20                   |