



Fixed Tray for 19" Rack with 600-800 mm Depth, 1RU

Designed for the easy installation of equipment that does not have a rack-mountable structure (routers, keyboards, computers, etc.).

Intended for installation in 19" racks with 600 mm depth. Its extendable rails allow mounting in 800 mm racks, although in this configuration the maximum load capacity is reduced. For installation in 800 mm racks requiring higher load capacity, the tray Ref. 533221 is recommended.

It has perforations in its base to facilitate the ventilation of the devices placed on it, as well as to allow them to be secured using Velcro straps or cable ties.

| | |
|---------------------|---------------|
| Ref. | 533220 |
| Logical ref. | UKS-L600 |
| EAN13 | 8424450335420 |

Other features

| | |
|-------------------|------------|
| Rack depth | 600-800 mm |
|-------------------|------------|

Packaging info

| | |
|------------|--------|
| Box | 1 pcs. |
|------------|--------|

Physical data

| | |
|---------------------|-----------------------|
| Net weight | 3,000.00 g |
| Gross volume | 11.97 dm ³ |
| Gross weight | 3,400.00 g |
| Width | 485.00 mm |
| Height | 44.00 mm |

| | |
|----------------------------|------------|
| Depth | 320.00 mm |
| Main product weight | 3,000.00 g |

Highlights

- Resistant material thanks to its fabrication of steel
- Extremely easy installation and use
- Extendable rails allowing installation in racks with 600 mm and 800 mm depth
- Designed as 1RU
- Includes 4 screws and 4 nuts for installation in a 19"-rack
- Black colour

Technical specifications : Ref. 533220

| | | |
|----------------------------|----|----------------------|
| Number of rack units (RU) | | 1 |
| Modular spacing (standard) | in | 19 |
| Width | in | 19.094 |
| Height | in | 1.732 |
| Depth | in | 12.598 |
| Sliding | | No |
| Max. load capacity | kg | 50 |
| Material | | Steel |
| Color | | Black |
| Surface finishing | | Electrostatic powder |