



19"-Rack Cabinet 15+2RU 600x600 mm

The 15+2RU rack Cabinet is used for the housing of active or passive equipment, visible from the outside and protected by a safe steel lockable structure. Compatible with optical fiber, data cables or coaxial cable installations, it allows the grouping of different technologies in a single cabinet.

Total capacity is 17RU, namely 15RU and an additional 2RU, taking advantage of the top and bottom ends. The rack is equipped with depth-adjustable side profiles, which allow the installation of different types of panels or equipment.

It has a reversible and removable front door with a flexible fit, which facilitates working in the rack. The tempered glass door allows viewing the status of the devices without opening the rack. It also has push-button removable side doors for access to the rack interior through the sides, an advantage when configuring rear connections.

It is designed for wall or floor installation. In addition, it includes a bracket for wall mounting. The independent bracket facilitates installation, since it allows marking the drilling points to screw it to the wall and, after that, to place the rack on it.

Ref.	533111
Logical ref.	MSR1915-66B
EAN13	8424450330937

Other features

Supply method Disassembled

Packaging info

Box 1 pcs.

Physical data

Net weight 35,000.00 g

Gross volume 277.56 dm³

Gross weight 36,500.00 g

Width 600.00 mm

Height 771.00 mm

Depth 600.00 mm

Main product weight 35,000.00 g

Highlights

- High strength and durability: made of steel, with a coating based on polyester resins and lead-free pigments
- Safety: Tempered glass, lockable hinged front door
- Laser marking: numerical identification of each "RU"
- Horizontal cable guides: 1RU cable panels located at the top and bottom of the cabinet to lead cabling from one side to the other and facilitate connections
- Additional supports: includes 2 side profiles as standard to reinforce shelf installation, especially in high-load configurations
- Electrical safety: Each door and removable panel includes a grounding screw (terminal) to ensure proper grounding connection
- A 120x120 mm ventilation kit can be incorporated for the installation of active equipment, such as headends
- High load capacity: supports up to 1000 kg when installed on the floor
- Black colour (RAL 9004)
- Black colour (RAL 9004)

Discover

REF.	DIMENSIONS (mm)	RACK UNITS (RU)	INSTALLATION	COMPATIBLE WITH			
				FAN	WHEELS	PLINTH	CABLE MANAGEMENT
533105/06	600x450	6+2					
533107/08	600x450	8+2					
533112/13	600x450	13+2	Wall/Floor	533174	Not applicable	Not applicable	
533114/15	600x450	15+2					
533111/16	600x600	15+2					
533120/18	600x600	18					533158
533121/22	600x600	22					533159
533126/27	600x600	27		533175			533160
533131/32	600x600	32					
533136/37	600x600	37					
533138/39	600x800	37					
533141/42	600x800	42	Floor		533171		533158
533128	800x800	27					533159
533143/44	800x800	42		533176		533401	533160
533140/45	800x800	42					Vertical 533166
533148/46	800x1000	42					533158
533149/47	800x1000	42				533402	533159
							533160
							Vertical 533167

Below is a compatibility table for our racks with all these accessories:

Technical specifications : Ref. 533111

Modular spacing (standard)	in	19
Height	in	30.354
Width	in	23.622
Depth	in	23.622
Number of rack units (RU)		15
Material		Steel
Thickness	in	0.047
Rack rail thickness	in	0.047
Color		Black
Surface finishing		Electrostatic powder
Number of doors		1
Front door material		Tempered glass
Rear door		No
Max. load capacity	kg	60
Removable sides		Yes
Installation type		Wall / Ground
Type of profile rail		L-shaped
Grounding		Yes
Protection index (IP)		20
Protection index (IK)		07