Tekniska specifikationer

Ref. 60060000

Number of leds		12					
Power	W	39					
Pre-programmed dimming		No					
Control interface		ON/OFF					
Optic type options		P	T2	T3	T4	ME	APZ	SCL
Lens type		PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens
Color temperature options		2200K	2700K	3000K	4000K	PC Amber
Luminous flux	lm	4426,5	4871,1	5382	5577	2281,5
Lighting efficiency	lm/W	113,5	124,9	138	143	58,5
LED current	mA	500	500	500	500	1000
Duration	h	100000					
Working life		L90B10					
Constant ligh output (CLO)		No					
Standard Deviation Colour Matching (SDCM)		< 3					
Color rendering index (CRI)		70					
CE Mark		Yes					
ENEC Certificate		No					
Protection Class IEC		Class II					
EU RoHS Compliant		Yes					
IK Rating (light module)		10					
IK Rating (whole luminaire)		10					
IP Rating (light module)		66					
IP Rating (whole luminaire)		66					
Colour		White/Grey					
Material		Tecnical Polymer					
Material cover		Without cover					
Fixation Material		Tecnical Polymer					
Mast diameter Max	mm	60					
Mast diameter Min	mm	42					
Mounting method		Post top/side entry					
Surface facing the wind	m^2	0,1151					
Number of LED modules		1					
Minimum power factor		0.9500					
Lighting source type		LED					
Replaceable light source		Yes					
Cable		Yes					
Power consumption tolerance	%	5					
Lighting flux tolerance	%	8					
Electric connection		3-pole waterproof connector					
Inrush current	A	26					
Input voltage	Vac	220 ... 240					
Mains frequency		50 Hz					
Max. Operating temperature	°C	40					
Min. Operating temperature	°C	-35					