Tekniska specifikationer

Ref. 60060001

Number of leds		12												
Power	W	39												
Pre-programmed dimming		Yes												
Control interface		1-10V												
Optic type options		P		T2		T3		T4		ME		APZ		SCL
Lens type		PC lens		PC lens		PC lens		PC lens		PC lens		PC lens		PC lens
Color temperature options		2200K		2700K				3000K		4000K				PC Amber
Luminous flux	lm	4426,5		4871,1				5382		5577				2281,5
Lighting efficiency	lm/W	113,5		124,9				138		143				58,5
LED current	mA	500		500				500		500				1000
Duration	h	100000												
Working life		L90B10												
Constant ligh output (CLO)		No												
Standard Deviation Colour Matching (SDCM)		< 3												
Color rendering index (CRI)		70												
CE Mark		Yes												
ENEC Certificate		No												
Protection Class IEC		Class II												
EU RoHS Compliant		Yes												
IK Rating (light module)		10												
IK Rating (whole luminaire)		10												
IP Rating (light module)		66												
IP Rating (whole luminaire)		66												
Colour		White/Grey												
Material		Tecnical Polymer												
Material cover		Without cover												
Fixation Material		Tecnical Polymer												
Mast diameter Max	mm	60												
Mast diameter Min	mm	42												
Mounting method		Post top/side entry												
Surface facing the wind	m^2	0,1151												
Number of LED modules		1												
Minimum power factor		0.9500												
Lighting source type		LED												
Replaceable light source		Yes												
Cable		Yes												
Power consumption tolerance	%	5												
Lighting flux tolerance	%	8												
Electric connection		3-pole waterproof connector												
Inrush current	A	26												
Input voltage	Vac	220 ... 240												
Mains frequency		50 Hz												
Max. Operating temperature	°C	40												
Min. Operating temperature	°C	-35												