Tekniska specifikationer

Ref. 63074100

Number of leds		12						
Power	W	40						
Pre-programmed dimming		Yes						
Control interface		Dali 2						
Optic type options		P	SP	T2	T3	T4	ME	APZ	SCL
Lens type		PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens
Color temperature options		2200K	2700K	3000K	4000K	PC Amber			
Luminous flux	lm	4240	4640	4840	5160	2120			
Lighting efficiency	lm/W	106	116	121	129	53			
LED current	mA	325	325	325	325	650			
Duration	h	100000						
Working life		L90B10						
Constant ligh output (CLO)		Yes						
Standard Deviation Colour Matching (SDCM)		< 3						
Color rendering index (CRI)		70						
CE Mark		Yes						
ENEC Certificate		No						
Protection Class IEC		Class II						
EU RoHS Compliant		Yes						
IK Rating (light module)		10						
IK Rating (whole luminaire)		9						
IP Rating (light module)		68						
IP Rating (whole luminaire)		56						
Colour		Black						
Material		Aluminium						
Material cover		Without cover						
Fixation Material		Aluminium						
Mast diameter Max	mm	60						
Mast diameter Min	mm	42						
Mounting method		Post top						
Surface protection		Powder coating						
Surface facing the wind	m^2	0,1602						
Number of LED modules		1						
Minimum power factor		0.9500						
Lighting source type		LED						
Replaceable light source		Yes						
Cable		Yes						
Power consumption tolerance	%	5						
Lighting flux tolerance	%	8						
Electric connection		3-pole waterproof connector						
Inrush current	A	26						
Input voltage	Vac	220 ... 240						
Mains frequency		50 Hz						
Max. Operating temperature	°C	40						
Min. Operating temperature	°C	-30						