Tekniska specifikationer

Ref. 63074200

Number of leds		12							
Power	W	40							
Pre-programmed dimming		Yes							
Control interface		Dali 2							
Optic type options		P	SP	T2	T3	T4	ME	APZ	SCL
Lens type		PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens
Color temperature options		2200K	2700K	3000K	4000K	PC Amber			
Luminous flux	lm	4200	4600	4800	5120	2080			
Lighting efficiency	lm/W	105	115	120	128	52			
LED current	mA	325	325	325	325	650			
Duration	h	100000							
Working life		L90B10							
Constant ligh output (CLO)		Yes							
Standard Deviation Colour Matching (SDCM)		< 3							
Color rendering index (CRI)		70							
CE Mark		Yes							
ENEC Certificate		No							
Protection Class IEC		Class II							
EU RoHS Compliant		Yes							
IK Rating (light module)		10							
IK Rating (whole luminaire)		9							
IP Rating (light module)		68							
IP Rating (whole luminaire)		56							
Colour		Black							
Material		Aluminium							
Material cover		Without cover							
Fixation Material		Aluminium							
Mast diameter Max	mm	60							
Mast diameter Min	mm	42							
Mounting method		Post top							
Surface protection		Powder coating							
Surface facing the wind	m^2	0,3							
Number of LED modules		1							
Minimum power factor		0.9500							
Lighting source type		LED							
Replaceable light source		Yes							
Cable		Yes							
Power consumption tolerance	%	5							
Lighting flux tolerance	%	8							
Electric connection		3-pole waterproof connector							
Inrush current	A	26							
Input voltage	Vac	220 ... 240							
Mains frequency		50 Hz							
Max. Operating temperature	°C	40							
Min. Operating temperature	°C	-35							