Tekniska specifikationer

Ref. 63081400

Number of leds		12													
Power	W	39													
Pre-programmed dimming		No													
Control interface		1-10V													
Node/sensor connection type		1x ANSI C136.41 Nema													
Optic type options		P		T2		T3		T4		ME		APZ		PX	SCL
Lens type		PC lens		PC lens		PC lens		PC lens		PC lens		PC lens		PMMA lens	PC lens
Color temperature options		2200K			2700K			3000K				4000K			PC Amber
Luminous flux	lm	4173			4563			4758				5070			1950
Lighting efficiency	lm/W	107			117			122				130			50
LED current	mA	500			500			500				500			1000
Duration	h	100000													
Working life		L90B10													
Constant ligh output (CLO)		No													
Standard Deviation Colour Matching (SDCM)		< 3													
Color rendering index (CRI)		70													
CE Mark		Yes													
ENEC Certificate		No													
Protection Class IEC		Class II													
EU RoHS Compliant		Yes													
IK Rating (light module)		8													
IK Rating (whole luminaire)		8													
IP Rating (light module)		66													
IP Rating (whole luminaire)		66													
Colour		Black													
Material		Aluminium													
Material cover		Transparent plastic													
Fixation Material		Aluminium													
Mounting method		Post top/side entry													
Surface protection		Powder coating													
Surface facing the wind	m^2	0,2112													
Number of LED modules		1													
Minimum power factor		0.9500													
Lighting source type		LED													
Replaceable light source		Yes													
Cable		Yes													
Power consumption tolerance	%	5													
Lighting flux tolerance	%	8													
Electric connection		3-pole waterproof connector													
Inrush current	A	26													
Input voltage	Vac	220 ... 240													
Mains frequency		50 Hz													
Max. Operating temperature	°C	40													
Min. Operating temperature	°C	-35													