Technical specifications

Ref. 63030000

Number of leds		12							
Power	W	39							
Pre-programmed dimming		No							
Control interface		ON/OFF							
Optic type options		P	SP	T2	T3	T4	ME	APZ	SCL
Lens type		PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens
Color temperature options		2200K		2700K		3000K		4000K	PC Amber
Luminous flux	lm	3744		3900		3989.7		4290	1950
Lighting efficiency	lm/W	96		100		102.3		110	50
LED current	mA	500		500		500		500	1000
Duration	h	100000							
Working life		L90B10							
Constant ligh output (CLO)		No							
Standard Deviation Colour Matching (SDCM)		< 3							
Color rendering index (CRI)		70							
CE Mark		Yes							
ENEC Certificate		No							
Protection Class IEC		Class II							
EU RoHS Compliant		Yes							
IK Rating (light module)		8							
IK Rating (whole luminaire)		8							
IP Rating (light module)		66							
IP Rating (whole luminaire)		56							
Color		Inox							
Material		stainless steel							
Material cover		Without cover							
Fixation Material		Stainless Steel							
Mounting method		Wall bracket							
Surface facing the wind	m²	0.113							
Number of LED modules		1							
Minimum power factor		0.9500							
Lighting source type		LED							
Replaceable light source		Yes							
Cable		Yes							
Power consumption tolerance	%	5							
Lighting flux tolerance	%	8							
Electric connection		3-pole waterproof connector							
Inrush current	A	26							
Input voltage	Vac	220 ... 240							
Mains frequency		50 Hz							
Max. Operating temperature	°F	104							
Min. Operating temperature	°F	-31							