Technical specifications

Ref. 68030001

Number of leds		12					
Power	W	39					
Pre-programmed dimming		Yes					
Control interface		1-10V					
Optic type options		P	T2	T3	T4	ME	APZ	SCL
Lens type		PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens
Color temperature options		2200K	2700K	3000K	4000K	PC Amber
Luminous flux	lm	4680	5070	5265	5850	2418
Lighting efficiency	lm/W	120	130	135	150	62
LED current	mA	500	500	500	500	1000
Duration	h	100000				
Working life		L90B10				
Constant ligh output (CLO)		No				
Standard Deviation Colour Matching (SDCM)		< 3				
Color rendering index (CRI)		70				
CE Mark		Yes				
ENEC Certificate		No				
Protection Class IEC		Class II				
EU RoHS Compliant		Yes				
IK Rating (light module)		10				
IK Rating (whole luminaire)		10				
IP Rating (light module)		68				
IP Rating (whole luminaire)		66				
Color		Aluminum				
Material		Aluminium				
Material cover		Without cover				
Fixation Material		Aluminium				
Mast diameter Max	in	2.362				
Mast diameter Min	in	1.654				
Mounting method		Post top/side entry				
Surface facing the wind	m^2	0.064				
Number of LED modules		1				
Minimum power factor		0.9500				
Lighting source type		LED				
Replaceable light source		Yes				
Cable		Yes				
Power consumption tolerance	%	5				
Lighting flux tolerance	%	8				
Electric connection		3-pole waterproof connector				
Inrush current	A	26				
Input voltage	Vac	220 ... 240				
Mains frequency		50 Hz				
Max. Operating temperature	°F	104				
Min. Operating temperature	°F	-31				