Tekniska specifikationer

Ref. 68330200

Number of leds		48												
Power	W	109												
Pre-programmed dimming		Yes												
Control interface		Dali 2												
Optic type options		P		T2		T3		T4		ME		APZ		SCL
Lens type		PC lens		PC lens		PC lens		PC lens		PC lens		PC lens		PC lens
Color temperature options		2200K		2700K			3000K			4000K			PC Amber	
Luminous flux	lm	13080		14170			14715			16350			6758	
Lighting efficiency	lm/W	120		130			135			150			62	
LED current	mA	340		340			340			340			680	
Duration	h	100000												
Working life		L90B10												
Constant ligh output (CLO)		Yes												
Standard Deviation Colour Matching (SDCM)		< 3												
Color rendering index (CRI)		70												
CE Mark		Yes												
ENEC Certificate		No												
Protection Class IEC		Class II												
EU RoHS Compliant		Yes												
IK Rating (light module)		10												
IK Rating (whole luminaire)		10												
IP Rating (light module)		68												
IP Rating (whole luminaire)		66												
Colour		Aluminum												
Material		Aluminium												
Material cover		Without cover												
Fixation Material		Aluminium												
Mast diameter Max	mm	60												
Mast diameter Min	mm	42												
Mounting method		Post top/side entry												
Surface facing the wind	m^2	0,096												
Number of LED modules		4												
Minimum power factor		0.9500												
Lighting source type		LED												
Replaceable light source		Yes												
Cable		Yes												
Power consumption tolerance	%	5												
Lighting flux tolerance	%	8												
Electric connection		3-pole waterproof connector												
Inrush current	A	65												
Input voltage	Vac	220 ... 240												
Mains frequency		50 Hz												
Max. Operating temperature	°C	40												
Min. Operating temperature	°C	-35												