Technical specifications

Ref. 68530000

Number of leds		72					
Power	W	165					
Pre-programmed dimming		No					
Control interface		ON/OFF					
Optic type options		P	T2	T3	T4	ME	APZ	SCL
Lens type		PC lens	PC lens	PC lens	PC lens	PC lens	PC lens	PC lens
Color temperature options		2200K	2700K	3000K	4000K	PC Amber
Luminous flux	lm	19800	21450	22275	24750	10230
Lighting efficiency	lm/W	120	130	135	150	62
LED current	mA	350	350	350	350	700
Duration	h	100000					
Working life		L90B10					
Constant ligh output (CLO)		No					
Standard Deviation Colour Matching (SDCM)		< 3					
Color rendering index (CRI)		70					
CE Mark		Yes					
ENEC Certificate		No					
Protection Class IEC		Class I					
EU RoHS Compliant		Yes					
IK Rating (light module)		10					
IK Rating (whole luminaire)		10					
IP Rating (light module)		68					
IP Rating (whole luminaire)		66					
Color		Aluminum					
Material		Aluminium					
Material cover		Without cover					
Fixation Material		Aluminium					
Mast diameter Max	in	2.362					
Mast diameter Min	in	1.654					
Mounting method		Post top/side entry					
Surface facing the wind	m^2	0.126					
Number of LED modules		6					
Minimum power factor		0.9500					
Lighting source type		LED					
Replaceable light source		Yes					
Cable		Yes					
Power consumption tolerance	%	5					
Lighting flux tolerance	%	8					
Electric connection		3-pole waterproof connector					
Inrush current	A	5.43					
Input voltage	Vac	220 ... 240					
Mains frequency		50 Hz					
Max. Operating temperature	°F	95					
Min. Operating temperature	°F	-31					