

Tekniska specifikationer : Ref. 769321

Number of Gigabit Ethernet ports (10/100/1000BASE-T)		2
Number of RF connectors		2
Number of G.hn domains		1
Max. number of nodes per G.hn domain		16
Bandwidth	MHz	200
Max. signal power	dBm/Hz	-76
Network protocols		802.1D Ethernet Bridge / IGMP (IPv4) Snooping / MLD (IPv6) Snooping / Quality of Service (QoS)
Wi-Fi standard		802.11 b/g/n (2x2) 2.4 GHz / 802.11 n/ac (2x2) 5 GHz
Number of WiFi antennas		4
OFDM Modulations		256-QAM
2.4GHz Channel bandwidth		40MHz
2.4GHz Antenna gain	dBi	4
5GHz Channel bandwidth		80MHz
5GHz Antenna gain	dBi	4
Wi-Fi encryption		WPA / WPA2 / WPA3
Impedance	Ω	75
Frequency range data	MHz	1 ... 200
Frequency range TV	MHz	290 ... 2350
Through losses TV	dB	< 1,5
DATA/TV feedthrough losses	dB	< 1,5
Return losses	dB	> 10
Power supply connector		Jack
Powering	Vdc	12
Max. power consumption	W	12
Operating temperature	°C	0 ... 40