

## Technical specifications : Ref. 237604

| Inputs                         |          | TERR       | V             | H            |
|--------------------------------|----------|------------|---------------|--------------|
| Frequency range                | MHz      | 47 ... 694 | 290 ... 2340  | 290 ... 2340 |
| Input level                    | dBmV     | 23 ... 35  | 10 ... 25     | 10 ... 25    |
| Equalizator                    | dB       | --         | 0 ... 12      | 0 ... 12     |
| Gain                           | dB       | --         | 18            | 18           |
| Number of MUX for Input level  |          | 24         | 52            | 52           |
| MUX bandwidth for Input level  | MHz      | 8          | 40            | 40           |
| Powering per inputs            | Vdc      | 12         | 12            | --           |
| Max. current pass              | mA       | 500        | 500           | --           |
| Max. current pass total inputs | mA       |            | 720           |              |
| Wavelength                     | nm       |            | 1550          |              |
| Optical output power           | dBmW     |            | 9             |              |
| Transmitter type               |          |            | MQW-DFB       |              |
| Optical connectors             |          |            | SC/APC        |              |
| RF connectors                  |          |            | "F" female    |              |
| Impedance                      | $\Omega$ |            | 75            |              |
| Input voltage                  | Vac      |            | 110 ... 230   |              |
| Mains frequency                |          |            | 50 Hz / 60 Hz |              |
| Current consumption            | mA       |            | < 320         |              |
| Max. power consumption         | W        |            | 18            |              |
| Operating temperature          | °F       |            | 23 ... 113    |              |