

## Tekniska specifikationer : Ref. 237605

| Inputs                         |      | TERR       | V             | H            |
|--------------------------------|------|------------|---------------|--------------|
| Frequency range                | MHz  | 47 ... 694 | 290 ... 2340  | 290 ... 2340 |
| Input level                    | dBµV | 83 ... 95  | 70 ... 85     | 70 ... 85    |
| Equalizator                    | dB   | --         | 0 ... 12      | 0 ... 12     |
| Gain                           | dB   | --         | 18            | 18           |
| Number of MUX for Input level  |      | 24         | 52            | 52           |
| MUX bandwidth for Input level  | MHz  | 8          | 40            | 40           |
| Powering per inputs            | Vdc  | 12         | 12            | --           |
| Max. current pass              | mA   | 500        | 500           | --           |
| Max. current pass total inputs | mA   |            | 720           |              |
| Wavelength                     | nm   |            | 1570          |              |
| Optical output power           | dBmW |            | 9             |              |
| Transmitter type               |      |            | MQW-DFB       |              |
| Optical connectors             |      |            | SC/APC        |              |
| RF connectors                  |      |            | "F" female    |              |
| Impedance                      | Ω    |            | 75            |              |
| Input voltage                  | Vac  |            | 110 ... 230   |              |
| Mains frequency                |      |            | 50 Hz / 60 Hz |              |
| Current consumption            | mA   |            | < 320         |              |
| Max. power consumption         | W    |            | 18            |              |
| Operating temperature          | °C   |            | -5 ... 45     |              |