

Tekniska specifikationer : Ref. 769530

Optical connectors		SC/APC
T-CONT Number		64
GEM Port Number		256
GPON Wavelength (@Downstream)	nm	1490
Optical input power	dBm	-33 ... -6
GPON Wavelength (@Upstream)	nm	1310
Optical output power	dBm	4,2
RF Overlay		Yes
Wavelength (@RF Overlay)	nm	1550
Optical input power RF Overlay	dBm	-10 ... -1
RF connectors		"F" female
RF Frequency range	MHz	47 ... 1220
RF output level	dBμV	70 ... 77
Number of Gigabit Ethernet ports (10/100/1000BASE-T)		4
Number of FXS ports		2
Number of USB ports		1
PoE Standard		IEEE 802.3af/at
Total PoE Power	W	50
Max Power per port	W	21
Switching capacity	Gbps	22,5
Number of VLANs		1024
MAC Addresses		4096
OMCI		Yes
Powering	Vdc	56
PSU input voltage	Vac	100 ... 240
Mains frequency		50 Hz / 60 Hz
Max PSU current input	A	2
Max PSU output current	A	1,07
Max. power consumption	W	60
Operating temperature	°C	0 ... 45

PoE-effekt på port 1: upp till 21 W, port 2 till 4: upp till 10 W.