Tekniska specifikationer

Ref. 63353100

Number of leds		48											
Power	W	70											
Pre-programmed dimming		No											
Control interface		Dali 2											
Optic type options													
Color temperature options		2200K		2700K		3000K		4000K		5000K		PC Amber	
Luminous flux	lm	8190		8960		9380		10010		10010		4200	
Lighting efficiency	lm/W	117		128		134		143		143		60	
LED current	mA	250	250	250	250	250	500	250					
Duration	h	100000											
Working life		L90B10											
Constant ligh output (CLO)		Yes											
Standard Deviation Colour Matching (SDCM)		< 3											
Color rendering index (CRI)		70											
CE Mark		Yes											
ENEC Certificate		No											
Protection Class IEC		Class I											
EU RoHS Compliant		Yes											
IK Rating (light module)		10											
IK Rating (whole luminaire)		10											
IP Rating (light module)		68											
IP Rating (whole luminaire)		66											
Colour		Black											
Material		Aluminium											
Material cover		Without cover											
Fixation Material		Aluminium											
Mounting method		Other											
Surface protection		Powder coating											
Number of LED modules		1											
Minimum power factor		0.9500											
Lighting source type		LED											
Replaceable light source		Yes											
Cable		Yes											
Power consumption tolerance	%	5											
Lighting flux tolerance	%	8											
Electric connection		3-pole waterproof connector											
Inrush current	A	2,15											
Input voltage	Vac	220 ... 240											
Mains frequency		50 Hz											
Max. Operating temperature	°C	40											
Min. Operating temperature	°C	-35											