

Technical specifications : Ref. 562621

Bands		FM	VHF	UHF	SAT
Frequency range	MHz	88 ... 108	174 ... 400	470 ... 694	950 ... 2150
High gain	dB	15	34	36	42
Low gain	dB	15	24	26	42
Gain adjustment range	dB	0 ... 20	0 ... 20	0 ... 20	0 ... 30
Noise figure	dB	6	5	7	--
Output level EN50083 IMD3 2tones -60dB	dBmV	60	61	62	62
Output level DIN45004B	dBmV	53	55	55	--
Output level EN50083 IMD3 2tones -60dB	dBmV	50	51	52	--
Output level EN50083 IMD2 2tones -60dB	dBmV	--	41	--	--
Equalizer	dB	--	--	--	0 ... 15
Powering per inputs	Vdc	0	12	12	--
Max current input	mA	0	200	200	--
Powering LNB - Local	Vdc	--	--	--	12
Max. local current for LNB	mA	--	--	--	400
Powering LNB - Remote	Vdc	--	--	--	12
Max. remote current for LNB	mA	--	--	--	500
Max. power consumption	W			12.5	
Max. current	mA			120	
Current consumption	mA			120	
Max power consumption (Inputr powering OFF)	W			6.5	
Max power consumption (Inputs powering ON)	W			12.5	
Input voltage	Vac			220 ... 230	
Mains frequency				50 Hz / 60 Hz	
Number of inputs				4	
Number of outputs				1	
Connectors				"EasyF" type	
Operating temperature	°F			23 ... 113	
Protection index (IP)				20	