Televes®

Technical specifications : Ref. 212201

Model		DK6000											
Type		U/UTP											
Euroclass		Fca											
Categorie		Cat 6											
Transmission bandwidth		250MHz											
Transfer rate		1Gbps											
Conductor Diameter	in	0.02											
Conductor Material		Solid copper											
Conductor type AWG		24											
Conductor isolation Diameter	in	0.037											
Conductor isolation Material		Polyethylene											
Crucifix filler		Yes											
Outer sheath Diameter	in	0.244											
Outer sheath Material		PE											
Outer sheath Thickness	in	0.022											
Rip cord		Yes											
Spark Test	Vac	3000											
Nominal impedance	Ω	100											
Conductor resistance	Ohm/100 m	< 9.38											
Nominal speed	%	72											
Working voltage	V	300											
Operating temperature	°F	-40 ... 176											
Frequencies		1 MHz	4 MHz	8 MHz	10 MHz	16 MHz	20 MHz	25 MHz	31,25 MHz	62,5 MHz	100 MHz	200 MHz	250 MHz
Attenuation (max.)	dB/100m	2	3.8	5.3	6	7.6	8.5	9.5	10.7	15.4	19.8	29	32.8
NEXT (min.)	dB/100m	74.3	65.3	60.8	59.3	56.2	54.8	53.3	51.9	47.4	44.3	39.8	38.3
PS NEXT (min.)	dB/100m	72.3	63.3	58.8	57.3	54.2	52.8	51.3	49.9	45.4	42.3	37.8	36.3
ACR-N (min.)	dB/100m	72.3	61.5	55.5	53.3	48.6	46.3	43.8	41.2	32	24.5	10.8	5.5
PS ACR-N (min.)	dB/100m	70.3	59.5	53.5	51.3	46.6	44.3	41.8	39.2	30	22.5	8.8	3.5
ACR-F (min.)	dB/100m	67.8	55.8	49.7	47.8	43.7	41.8	39.8	37.9	31.9	27.8	21.8	19.8
PS ACR-F (min.)	dB/100m	64.8	52.8	46.7	44.8	40.7	38.8	36.8	34.9	28.9	24.8	18.8	16.8
Return losses (min.)	dB	20	23	24.5	25	25	25	24.3	23.6	21.5	20.1	18	17.3