

Technical specifications : Ref. 212302

Model																				DK6000
Type																				U/UTP
Euroclass																				Dca
Euroclass: Smoke Production																				s2
Euroclass: Flaming droplets																				d2
Euroclass: Acidity																				a1
Categorie																				Cat 6
Transmission bandwidth																				400MHz
Transfer rate																				1Gbps
Conductor Diameter																				0.022
Conductor Material																				Solid copper
Conductor type AWG																				23
Conductor isolation Diameter																				0.04
Conductor isolation Material																				Polyethylene
Crucifix filler																				Yes
Outer sheath Diameter																				0,244
Outer sheath Material																				LSFH
Outer sheath Thickness																				0.02
Rip cord																				Yes
Spark Test																				Vac
Nominal impedance																				Ω
Conductor resistance																				Ohm/100m
																				m
																				< 9.38
Nominal speed																				%
Working voltage																				V
Operating temperature																				°F
																				-13 ... 158
Frequencies																				
		1 MHz	4 MHz	8 MHz	10 MHz	16 MHz	20 MHz	25 MHz	31,25 MHz	62,5 MHz	100 MHz	200 MHz	250 MHz	300 MHz	400 MHz					
Attenuation (max.)	dB/100m	2	3.8	5.3	6	7.6	8.5	9.5	10.7	15.4	19.8	29	32.8	--	--					
Attenuation (typ.)	dB/100m	1.7	3.5	5	5.6	7.1	8	8.9	10	14.4	18.3	26.2	29.4	32.8	37.7					
NEXT (min.)	dB/100m	74.3	65.3	60.8	59.3	56.2	54.8	53.3	51.9	47.4	44.3	39.8	38.3	--	--					
NEXT (typ.)	dB/100m	87.3	78.1	74.1	70.1	67.3	65.9	64.1	62.2	57.3	57	50.5	49.5	44	36.5					
PS NEXT (min.)	dB/100m	72.3	63.3	58.8	57.3	54.2	52.8	51.3	49.9	45.4	42.3	37.8	36.3	--	--					
PS NEXT (typ.)	dB/100m	84.9	76.2	71.2	67.7	64.8	64.1	62.9	60.5	56.1	52.1	46.5	45.3	41.2	35.6					
ACR-N (min.)	dB/100m	72.3	61.5	55.5	53.3	48.6	46.3	43.8	41.2	32	24.5	10.8	5.5	--	--					
ACR-N (typ.)	dB/100m	85.5	74.4	69.1	64	59.9	57.9	55.3	52.2	43	36.1	22.7	19.2	11.2	-1.2					
PS ACR-N (min.)	dB/100m	70.3	59.5	53.5	51.3	46.6	44.3	41.8	39.2	30	22.5	8.8	3.5	--	--					
PS ACR-N (typ.)	dB/100m	83.2	71.8	66.2	62	57.6	56.2	54.1	50.5	41.5	34.4	20.3	16	9	-1.7					
ACR-F (min.)	dB/100m	67.8	55.8	49.7	47.8	43.7	41.8	39.8	37.9	31.9	27.8	21.8	21.8	--	--					
ACR-F (typ.)	dB/100m	78.1	66	60.9	58.7	54.3	52.5	50.4	49	41.6	38.6	30.5	30.5	23.9	22.3					
PS ACR-F (min.)	dB/100m	64.8	52.8	46.7	44.8	40.7	38.8	36.8	34.9	28.9	24.8	18.8	16.8	--	--					
PS ACR-F (typ.)	dB/100m	74.7	63.2	58.1	56.2	52.9	50.4	48.4	46.5	40.3	35.8	28.6	26.8	20.5	16.5					
Return losses (min.)	dB	20	23	24.5	25	25	25	24.3	23.6	21.5	20.1	18	17.3	--	--					
Return losses	dB	25.6	26.6	29.3	29.8	31.9	32.3	32.1	32.5	31.6	27.7	24.8	23.1	21.8	19.3					