# Tekniska specifikationer

**Ref. 212502**

| | | |
|---|---|---|
| Model | | T-100 |
| Cable type | | RG-6 |
| Standard | | EN 50117-10-2 |
| Euroclass | | Fca |
| Class | | A |
| Inner conductor Diameter | mm | 1,13 |
| Inner conductor Material | | Copper (Cu) |
| Inner conductor Resistance | Ohm/km | < 20 |
| Dielectric Diameter | mm | 4,7 |
| Dielectric Material | | Foam polyethylene (PEE) |
| Dielectric Color | | White RAL 9003 |
| Overlapped foil | | Aluminium + Polyester + Aluminium |
| Braid Material | | Aluminium |
| Braid dimensions: No. of carriers (Nc) | | 16 |
| Braid Dimensions: No. of strands per carrier (Ns) | | 8 |
| Braid Dimensions: strand diameter (Ø) | mm | 0,12 |
| Braid Resistance | Ohm/km | < 27 |
| Braid Coverage | % | 77 |
| 2nd foil | | No |
| 2nd foil glued to the dielectric | | No |
| Petrol-Jelly | | No |
| Anti-migrating film | | No |
| Outer sheath Diameter | mm | 6,6 |
| Outer sheath Material | | PE |
| Minimum bending radius | mm | 33 |
| Transfer impedance (5-30MHz) | mΩ /m | < 5 |
| 1GHz shielding | dB | > 85 |
| Spark Test | Vac | 3000 |
| Capacitance | pF/m | 52 |
| Impedance | Ω | 75 |
| Velocity ratio | % | 85 |
| Operating temperature | °C | -40 ... 80 |
| Atenuacion 5MHz | dB/m | 0,02 |
| Atenuacion 47MHz | dB/m | 0,05 |
| Atenuacion 54MHz | dB/m | 0,05 |
| Atenuacion 90MHz | dB/m | 0,06 |
| Atenuacion 200MHz | dB/m | 0,08 |
| Atenuacion 500MHz | dB/m | 0,14 |
| Atenuacion 698MHz | dB/m | 0,15 |
| Atenuacion 800MHz | dB/m | 0,16 |
| Atenuacion 862MHz | dB/m | 0,17 |
| Atenuacion 950MHz | dB/m | 0,18 |
| Atenuacion 1000MHz | dB/m | 0,19 |
| Atenuacion 1220MHz | dB/m | 0,21 |
| Atenuacion 1350MHz | dB/m | 0,23 |
| Atenuacion 1750MHz | dB/m | 0,25 |
| Atenuacion 2050MHz | dB/m | 0,28 |
| Atenuacion 2150MHz | dB/m | 0,29 |
| Atenuacion 2200MHz | dB/m | 0,29 |
| Atenuacion 2300MHz | dB/m | 0,3 |
| Atenuacion 2400MHz | dB/m | 0,31 |
| Atenuacion 3000MHz | dB/m | 0,34 |
| Return losses 5MHz | dB | 23 |
| Return losses 47MHz | dB | 23 |
| Return losses 54MHz | dB | 23 |
| Return losses 90MHz | dB | 23 |
| Return losses 200MHz | dB | 23 |
| Return losses 500MHz | dB | 20 |
| Return losses 698MHz | dB | 20 |
| Return losses 800MHz | dB | 20 |
| Return losses 862MHz | dB | 20 |
| Return losses 950MHz | dB | 20 |
| Return losses 1000MHz | dB | 20 |
| Return losses 1220MHz | dB | 18 |
| Return losses 1350MHz | dB | 18 |
| Return losses 1750MHz | dB | 18 |
| Return losses 2050MHz | dB | 16 |
| Return losses 2150MHz | dB | 16 |
| Return losses 2200MHz | dB | 16 |
| Return losses 2300MHz | dB | 16 |
| Return losses 2400MHz | dB | 16 |
| Return losses 3000MHz | dB | 16 |