

Tekniska specifikationer : Ref. 2361

| | | |
|--------------------------------------|-------|---|
| Fiber core type | | Single-mode (ITU-T-G.657A2) |
| Optical fiber type category | | OS1 |
| Fiber core diameter | µm | 9 |
| Fiber cladding diameter | µm | 125 |
| Coating buffer diameter | µm | 250 |
| Cable structure | | Tight buffer |
| Plastic buffer diameter | mm | 0,8 |
| Outer sheath Diameter | mm | 3 |
| Outer sheath Material | | LSFH |
| Blocking jelly | | No |
| Attenuation 1310nm | dB/km | < 0,4 |
| Attenuation 1490nm | dB/km | < 0,4 |
| Attenuation 1550nm | dB/km | < 0,3 |
| Insertion losses in connector 1 | dB | < 0,3 |
| Insertion losses in connector 2 | dB | < 0,3 |
| Return losses in connector 1 | dB | > 50 |
| Return losses in connector 2 | dB | > 50 |
| Optical connector type 1 | | FC |
| Polishing type (Optical connector 1) | | UPC |
| Optical connector type 2 | | FC |
| Polishing type (Optical connector 2) | | UPC |
| Short tension | N | 440 |
| Structure reinforcement element | | Aramid fibers and flexible stainless steel tube |
| Short crush (@100mm) | N | 1000 |
| Minimum bending radius | mm | 30 |
| Operating temperature | °C | -20 ... 70 |