

Technical specifications : Ref. 385101

| | | | | | | | | | | | | | | | | | | | | | |
|---|------|-----------------------------------|--------|--------|--------|---------|---------|---------|---------|---------|---------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|
| Type | | SK2000plus | | | | | | | | | | | | | | | | | | | |
| Standard | | EN 50117-2-4 | | | | | | | | | | | | | | | | | | | |
| Euroclass | | Eca | | | | | | | | | | | | | | | | | | | |
| Class | | A++ | | | | | | | | | | | | | | | | | | | |
| Inner conductor Diameter | mm | 1.02 | | | | | | | | | | | | | | | | | | | |
| Inner conductor Material | | Copper (Cu) | | | | | | | | | | | | | | | | | | | |
| Inner conductor Resistance | Ω/km | < 22 | | | | | | | | | | | | | | | | | | | |
| Dielectric Diameter | mm | 4.6 | | | | | | | | | | | | | | | | | | | |
| Dielectric Material | | Foam polyethylene (PEE) | | | | | | | | | | | | | | | | | | | |
| Dielectric Color | | White RAL 9003 | | | | | | | | | | | | | | | | | | | |
| Overlapped foil | | Aluminium + Polyester + Aluminium | | | | | | | | | | | | | | | | | | | |
| Braid Material | | Tinned copper (CuSn) | | | | | | | | | | | | | | | | | | | |
| Braid dimensions: No. of carriers (Nc) | | 24 | | | | | | | | | | | | | | | | | | | |
| Braid Dimensions: No. of strands per carrier (Ns) | | 7 | | | | | | | | | | | | | | | | | | | |
| Braid Dimensions: strand diameter (Ø) | mm | 0.1 | | | | | | | | | | | | | | | | | | | |
| Braid Resistance | Ω/km | < 10.5 | | | | | | | | | | | | | | | | | | | |
| Braid Coverage | % | 82 | | | | | | | | | | | | | | | | | | | |
| 2nd foil | | Yes | | | | | | | | | | | | | | | | | | | |
| 2nd foil glued to the dielectric | | No | | | | | | | | | | | | | | | | | | | |
| Petrol-Jelly | | No | | | | | | | | | | | | | | | | | | | |
| Anti-migrating film | | No | | | | | | | | | | | | | | | | | | | |
| Outer sheath Diameter | mm | 6.7 | | | | | | | | | | | | | | | | | | | |
| Outer sheath Material | | PVC | | | | | | | | | | | | | | | | | | | |
| Outer sheath Thickness | mm | 0.3 | | | | | | | | | | | | | | | | | | | |
| Minimum bending radius | mm | 33.5 | | | | | | | | | | | | | | | | | | | |
| Transfer impedance (5-30MHz) | mΩ/m | < 0.9 | | | | | | | | | | | | | | | | | | | |
| 1GHz shielding | dB | > 105 | | | | | | | | | | | | | | | | | | | |
| Connector type 1 | | "F" Compression | | | | | | | | | | | | | | | | | | | |
| Connector type 2 | | "F" Compression | | | | | | | | | | | | | | | | | | | |
| Spark Test | Vac | 3000 | | | | | | | | | | | | | | | | | | | |
| Capacitance | pF/m | 54 | | | | | | | | | | | | | | | | | | | |
| Impedance | Ω | 75 | | | | | | | | | | | | | | | | | | | |
| Velocity ratio | % | 84 | | | | | | | | | | | | | | | | | | | |
| Operating temperature | °C | -30 ... 70 | | | | | | | | | | | | | | | | | | | |
| Frequencies | | 5 MHz | 47 MHz | 54 MHz | 90 MHz | 200 MHz | 500 MHz | 698 MHz | 800 MHz | 862 MHz | 950 MHz | 1000 MHz | 1220 MHz | 1350 MHz | 1750 MHz | 2050 MHz | 2150 MHz | 2200 MHz | 2300 MHz | 2400 MHz | 3000 MHz |
| Attenuation (typ.) | dB/m | 0.02 | 0.05 | 0.05 | 0.06 | 0.09 | 0.14 | 0.17 | 0.19 | 0.19 | 0.19 | 0.21 | 0.22 | 0.25 | 0.28 | 0.3 | 0.31 | 0.31 | 0.32 | 0.33 | 0.36 |