

Tekniska specifikationer : Ref. 719602

| | | |
|--|------------|--------------|
| Number of inputs | | 9 |
| Number of cascable outputs | | 9 |
| Number of user outputs | | 12 |
| Frequency range TERR. | MHz | 88 ... 862 |
| Frequency range SAT. | MHz | 950 ... 2400 |
| Input level TERR. | dB μ V | 80 ... 110 |
| Input level SAT. | dB μ V | 65 ... 112 |
| Through losses TERR. | dB | < 4 |
| Through losses SAT. | dB | 2 ... 3,5 |
| Tap losses TERR. Active | dB | 1 |
| Tap losses TERR. Passive | dB | 32 |
| Tap losses SAT. HG | dB | 0 |
| Tap losses SAT. LG | dB | 14 ... 8 |
| Output level 10Ch DVB-T | dB μ V | 78 |
| Isolation H/V | dB | > 50 |
| Isolation users | dB | > 30 |
| Powering | Vdc | 12 ... 18 |
| Max. current (PSU - TERR ACT.) | mA | 115 |
| Max. current with loaded outputs (PSU - TERR ACT.) | mA | 160 |
| Max. current (PSU - TERR PAS.) | mA | 5 |
| Max. current (STB) | mA | 85 |
| Operating temperature | °C | -5 ... 45 |
| Protection index (IP) | | 20 |