

Technical specifications : Ref. 714605

| | | |
|----------------------------|------|--------------|
| Number of inputs | | 9 |
| Number of cascable outputs | | 9 |
| Number of user outputs | | 32 |
| Frequency range TERR. | MHz | 88 ... 862 |
| Frequency range SAT. | MHz | 950 ... 2400 |
| Input level TERR. | dBmV | 0.09 |
| Input level SAT. | dBmV | 0.112 |
| Through losses TERR. | dB | 8 |
| Through losses SAT. | dB | 8 ... 18 |
| Tap losses 1...8 TERR. | dB | 4 |
| Tap losses 1...8 SAT. | dB | 0 |
| Tap losses 9...16 TERR. | dB | 6 |
| Tap losses 9...16 SAT. | dB | 4 |
| Tap losses 17...24 TERR. | dB | 8 |
| Tap losses 17...24 SAT. | dB | 8 |
| Tap losses 25...32 TERR. | dB | 10 |
| Tap losses 25...32 SAT. | dB | 12 |
| Isolation H/V | dB | > 30 |
| Isolation users | dB | > 25 |
| Powering | Vdc | 12 |
| Max. current (PSU - LG) | mA | 170 |
| Max. current (PSU - HG) | mA | 355 |
| Max. current (STB) | mA | 35 |
| Operating temperature | °F | 23 ... 113 |
| Protection index | | 20 |