

## Technical specifications : Ref. 719403

|  |      |              |
|--|------|--------------|
| Number of inputs                                   |      | 5            |
| Number of cascable outputs                         |      | 5            |
| Number of user outputs                             |      | 8            |
| Frequency range TERR.                              | MHz  | 88 ... 862   |
| Frequency range SAT.                               | MHz  | 950 ... 2400 |
| Input level TERR.                                  | dBmV | 20 ... 50    |
| Input level SAT.                                   | dBmV | 5 ... 52     |
| Through losses TERR.                               | dB   | < 2          |
| Through losses SAT.                                | dB   | < 2          |
| Tap losses TERR. Active                            | dB   | 0 ... 4      |
| Tap losses TERR. Passive                           | dB   | 32           |
| Tap losses SAT. HG                                 | dB   | 2 ... 7      |
| Tap losses SAT. LG                                 | dB   | 12 ... 14    |
| Output level 10Ch DVB-T                            | dBmV | 18           |
| Isolation H/V                                      | dB   | > 50         |
| Isolation users                                    | dB   | > 30         |
| Powering   | Vdc  | 12 ... 18    |
| Max. current (PSU - TERR ACT.)                     | mA   | 65           |
| Max. current with loaded outputs (PSU - TERR ACT.) | mA   | 110          |
| Max. current (PSU - TERR PAS.)                     | mA   | 5            |
| Max. current (STB)                                 | mA   | 85           |
| Operating temperature                              | °F   | 23 ... 113   |
| Protection index (IP)                              |      | 20           |