

Tekniska specifikationer : Ref. 209032

Type			U/UTP											
Categorie			Cat 6											
Transmission bandwidth			250MHz											
Transfer rate			1Gbps											
Conductor Diameter	mm		0,2											
Conductor Material			Flexible copper											
Conductor type AWG			24											
Conductor isolation Diameter	mm		0,96											
Conductor isolation Material			Polyethylene											
Crucifix filler			Yes											
Outer sheath Diameter	mm		6											
Outer sheath Material			LSFH											
Outer sheath Thickness	mm		0,6											
Rip cord			No											
Cable length	m		1											
Data connector type			RJ45											
Spark Test	Vac		3000											
Nominal impedance	Ω		100											
Conductor resistance	Ohm/km		< 117											
Nominal speed	%		72											
Working voltage	V		300											
Operating temperature	°C		-30 ... 70											
Frequencies			1 MHz	4 MHz	8 MHz	10 MHz	16 MHz	20 MHz	25 MHz	31.25 MHz	62.5 MHz	100 MHz	200 MHz	250 MHz
Attenuation (max.)	dB/100m	--	--	--	--	--	--	--	--	--	--	--	31,7	--
Return losses	dB	19	19	19	19	18	17,5	17	16,5	14	12	9	8	