Technical specifications

Ref. 70010000

Number of leds		12				
Power	W	15				
Pre-programmed dimming		No				
Control interface		ON/OFF				
Optic type options		SP				
Lens type		PC protector				
Color temperature options		2200K	2700K	3000K	4000K	PC Amber
Luminous flux	lm	750	795	823	900	360
Lighting efficiency	lm/W	50	53	55	60	24
LED current	mA	200	200	200	200	400
Duration	h	100000				
Working life		L90B10				
Constant ligh output (CLO)		No				
Standard Deviation Colour Matching (SDCM)		< 3				
Color rendering index (CRI)		70				
CE Mark		Yes				
ENEC Certificate		No				
Protection Class IEC		Class II				
EU RoHS Compliant		Yes				
Energy efficiency class (EU2019/215)		A				
IK Rating (light module)		10				
IK Rating (whole luminaire)		10				
IP Rating (light module)		65				
IP Rating (whole luminaire)		65				
Material		Thermopine wood and stainless steel AISI 304				
Material cover		Opaque plastic				
Mounting method		Other				
Number of LED modules		1				
Minimum power factor		0.9500				
Lighting source type		LED				
Replaceable light source		Yes				
Cable		Yes				
Power consumption tolerance	%	8				
Lighting flux tolerance	%	8				
Electric connection		3-pole waterproof connector				
Input voltage	Vac	220 ... 240				
Mains frequency		50 Hz				
Max. Operating temperature	°F	104				
Min. Operating temperature	°F	-31				